

SK-FLOORING INC

SIZE : 9"*60" *8MM /20 MIL

Planks per Carton-6/Sq.Ft. per Carton-22.72		
Lifetime residential warranty-50year light commercial warranty		
FloorScore™ Certified / Uniclic™ Click System		
<u>Tested For</u>	<u>Test Performed</u>	<u>Result</u>
Slip Resistance	DIN 51130 EN13893	R10 DS
Reaction to fire class	EN ISO 9239-1 EN ISO 11925-2	Bfl-s1
Static Load	EN 433/ASTM F970-07	Pass
Coefficient of Function	DIN 51130/ASTM D2047-04	Pass
Smoke Density	ASTM E662-09	Pass
Short Term Indentation	ASTM F1914-98	Pass
Stain Resistance	ASTM F928	Pass
Peel Resistance	EN 431	Pass
Shear Resistance	EN 532	Pass
Color Fastness	EN 649	Pass
Wear Resistance	EN 431	High
IIC/STC Rating	ASTM E492-90/ASTM E90-2009	68db/65db
Dimensional Stability	ASTM F2199-09 (R2014)	shrinkage< 0.002% Curling <0.2mm
Phthalates (DBP/BBP/DEHP/DINP/DNOP/DI00)	EN14372:2004	None Detected